

lamaPLC: MLX90614 infrared non-contact thermometer

The MLX90614 is an infrared thermometer for non-contact temperature measurements. Both the IR-sensitive thermopile detector chip and the signal conditioning ASIC are integrated in the same TO-39 can. Integrated into the MLX90614 are a low noise amplifier, 17-bit ADC and powerful DSP unit thus achieving high accuracy and resolution of the thermometer.

The thermometer comes factory-calibrated with a digital SMBus output, providing full access to the measured temperature across the complete temperature range(s) with a resolution of 0.02°C.

The user can configure the digital output to use pulse-width modulation (PWM). As a standard, the 10-bit PWM is configured to continuously transmit the measured temperature in range of -20 to 120°C, with an output resolution of 0.14°C.

MLX90614 Features

- Factory calibrated in a wide temperature range: -40 to 125°C for sensor temperature and -70 to 380°C for object temperature
- High accuracy of 0.5°C over a wide temperature range (0..+50 C for both Ta and To)
- Medical accuracy of 0.1°C in a limited temperature range available on request
- Measurement resolution of 0.02°C
- Single and dual zone versions
- SMBus-compatible digital interface for rapid temperature readings and building sensor networks
- Customizable PWM output for continuous reading
- Available in 3V and 5V versions
- Simple adaptation for 8 to 16V applications
- Power saving mode
- Different package options for applications and measurement versatility
- Automotive grade

From:

<https://lamaplc.com/> - lamaPLC

Permanent link:

<https://lamaplc.com/doku.php?id=sensor:mlx90614&rev=1778191412>

Last update: **2026/05/08 00:03**

